

50CT

Step-By-Step Installation Guide To Replace NSA 50C

Item Check List

1. 50CT
2. Faucet diverter head with tubing
3. Faucet adaptors
4. O-Rings
5. Compression fitting set
6. Warranty sticker



Tools needed: Crescent Wrench (Not included)

Instructions for Replacing NSA Model 50C

50CT INSTALLATION INSTRUCTION'S

- 1** Please locate faucet and remove the aerator.



- 2** Connect diverter to faucet.
- It may be required to use one of the adaptor rings provided. (Ensure the appropriate O-Ring is installed between the faucet head and the adaptor and between the adaptor and the diverter)
 - Do not discard any parts in the event that they are needed after a remodel or if you are traveling.

- 3** Remove nut from filter.



- 4** Place nut on tubing followed by the Delrin sleeve.
- Insert tubing into fitting on filter sliding down nut and sleeve to filter.
 - Hand tighten the compression nut.
 - Once nut is hand tightened, give the compression fitting a half turn with a wrench. (Note: If compression nut is over tightened, the water will not flow properly. You will be able to determine this, if the filter has a loud audible sound when water flows out of it.)



- 5** Insert faucet into the top of the filter. You may need to rotate the spout while applying pressure to ensure proper installation.



- 6 DO NOT** forget to **FLUSH** the filter before using.
- Place the filter in the sink.
 - Turn the water on at 1/4 pressure and activate the diverter. This will saturate the filter with water. Wait till water starts to come out of the spout.
 - Turn your faucet to half pressure and allow the water to run for 5 to 10 minutes. This process should remove all the carbon dust. Please repeat the process if you are seeing carbon dust.
 - As you flush your filter, check all the fittings to ensure that there are no leaks. If you have a leak, remember DO NOT over tighten. Recommended to tighten slowly till water stops dripping.

Note: Your water may come out cloudy when first installed. You are perfectly safe, this is just air trapped in the filter. It could take up to 2 weeks for the unit to fully be saturated with water.

239.643.2215

WM FILTER

www.wmfilter.com



Enjoy clean drinking water!

Please remember to mark the date of installation and replacement date on the sticker provided in the box.

WM Filter
Replacement Reminder

Model No.

Installation Date

Replacement Date

(Estimated 3 yrs from installation date)

Cold Water Only!

1.800.959.0708